

### 6<sup>5</sup>/<sub>8</sub> in 24 lb/ft TX22-125 (S31803)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

#### PIPE BODY CHARACTERISTICS

Nominal OD	6.625 in
Nominal ID	5.921 in
Min. Yield Strength	125 ksi
Nominal Wall Thickness	0.352 in
Minimum Wall Thickness	90 %
Drift	5.796 in

#### CONNECTION PROPERTIES

Coupling OD (nominal)	7.283 in
Coupling ID (nominal)	5.846 in
Make-up Loss	4.921 in
Coupling Length	10.866 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

#### CONNECTION PERFORMANCE

Tensile Yield Load	867 klb
Compression Yield Load	694 klb
Internal Yield Pressure	11 950 psi
External Pressure Resistance	7 020 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	418 klb

#### TORQUE VALUES

Minimum Make-up torque	14 340 ft-lb
Optimum Make-up torque	15 930 ft-lb
Maximum Make-up torque	17 520 ft-lb
Minimum Shoulder Torque	800 ft-lb
Maximum Shoulder Torque	800 ft-lb
Maximum Operational Torque	15 930 ft-lb

Connection qualified as per ISO 13679:2002 - CAL IV



[www.sentinelconnections.com](http://www.sentinelconnections.com)

PCTDS-SENTINEL\_One-6.625-24-TX22-125

Date of issue (dd/mm/yyyy): 31/10/2024

**TUBACEX**  
GROUP