

5½ in 26.8 lb/ft TX25NP-80 (S32750)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	5.500 in
Nominal ID	4.500 in
Min. Yield Strength	80 ksi
Nominal Wall Thickness	0.500 in
Minimum Wall Thickness	87.5 %
Drift	4.375 in

CONNECTION PROPERTIES

Coupling OD (nominal)	6.283 in
Coupling ID (nominal)	4.434 in
Make-up Loss	4.413 in
Coupling Length	10.748 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	628 klb
Compression Yield Load	628 klb
Internal Yield Pressure	12 730 psi
External Pressure Resistance	13 220 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	403 klb

TORQUE VALUES

Minimum Make-up torque	13 010 ft-lb
Optimum Make-up torque	14 460 ft-lb
Maximum Make-up torque	15 900 ft-lb
Minimum Shoulder Torque	720 ft-lb
Maximum Shoulder Torque	720 ft-lb
Maximum Operational Torque	17 350 ft-lb

Connection qualified as per ISO 13679:2002 - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_One-5.5-26.8-TX25NP-80

Date of issue (dd/mm/yyyy): 31/10/2024

TUBACEX
GROUP