

## 7 in 29 lb/ft TX25NP-80 (S32750)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

### PIPE BODY CHARACTERISTICS

Nominal OD	7.000 in
Nominal ID	6.184 in
Min. Yield Strength	80 ksi
Nominal Wall Thickness	0.408 in
Minimum Wall Thickness	87.5 %
Drift	6.059 in

### CONNECTION PROPERTIES

Coupling OD (nominal)	7.671 in
Coupling ID (nominal)	6.109 in
Make-up Loss	4.761 in
Coupling Length	11.535 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

### CONNECTION PERFORMANCE

Tensile Yield Load	676 klb
Compression Yield Load	676 klb
Internal Yield Pressure	8 160 psi
External Pressure Resistance	7 030 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	415 klb

### TORQUE VALUES

Minimum Make-up torque	14 340 ft-lb
Optimum Make-up torque	15 930 ft-lb
Maximum Make-up torque	17 520 ft-lb
Minimum Shoulder Torque	800 ft-lb
Maximum Shoulder Torque	800 ft-lb
Maximum Operational Torque	19 120 ft-lb

Connection qualified as per ISO 13679:2002 - CAL IV



[www.sentinelconnections.com](http://www.sentinelconnections.com)

PCTDS-SENTINEL\_One-7-29-TX25NP-80

Date of issue (dd/mm/yyyy): 31/10/2024

**TUBACEX**  
GROUP