

**4½ in 13.5 lb/ft TX25NP-80 (S32750)**

**Box end finish: Cu-Plating Lubrication: API-Modified**

**Clearance: Standard Bevel: 45°**

**PIPE BODY CHARACTERISTICS**

Nominal OD	4.500 in
Nominal ID	3.920 in
Min. Yield Strength	80 ksi
Nominal Wall Thickness	0.290 in
Minimum Wall Thickness	87.5 %
Drift	3.795 in

**CONNECTION PROPERTIES**

Coupling OD (nominal)	4.969 in
Coupling ID (nominal)	3.873 in
Make-up Loss	3.342 in
Coupling Length	7.441 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

**CONNECTION PERFORMANCE**

Tensile Yield Load	307 klb
Compression Yield Load	307 klb
Internal Yield Pressure	9 020 psi
External Pressure Resistance	8 540 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	170 klb

**TORQUE VALUES**

Minimum Make-up torque	4 450 ft·lb
Optimum Make-up torque	4 940 ft·lb
Maximum Make-up torque	5 440 ft·lb
Minimum Shoulder Torque	250 ft·lb
Maximum Shoulder Torque	250 ft·lb
Maximum Operational Torque	5 930 ft·lb

**Connection qualified as per ISO 13679:2002 - CAL IV**



[www.sentinelconnections.com](http://www.sentinelconnections.com)

PCTDS-SENTINEL\_One-4.5-13.5-TX25NP-80

Date of issue (dd/mm/yyyy): 31/10/2024

**TUBACEX**  
GROUP