

5 in 15 lb/ft TX28-110 (N08028)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	5.000 in
Nominal ID	4.408 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.296 in
Minimum Wall Thickness	90 %
Drift	4.283 in

CONNECTION PROPERTIES

Coupling OD (nominal)	5.470 in
Coupling ID (nominal)	4.344 in
Make-up Loss	4.191 in
Coupling Length	10.394 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	481 klb
Compression Yield Load	385 klb
Internal Yield Pressure	11 720 psi
External Pressure Resistance	8 850 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	177 klb

TORQUE VALUES

Minimum Make-up torque	6 040 ft-lb
Optimum Make-up torque	6 710 ft-lb
Maximum Make-up torque	7 380 ft-lb
Minimum Shoulder Torque	340 ft-lb
Maximum Shoulder Torque	340 ft-lb
Maximum Operational Torque	8 050 ft-lb

Connection qualified as per ISO 13679:2002 - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_One-5-15-TX28-110

Date of issue (dd/mm/yyyy):

31/10/2024

TUBACEX
GROUP