

7⁵/₈ in 33.7 lb/ft TX28-110 (N08028)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	7.625 in
Nominal ID	6.765 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.430 in
Minimum Wall Thickness	90 %
Drift	6.640 in

CONNECTION PROPERTIES

Coupling OD (nominal)	8.305 in
Coupling ID (nominal)	6.700 in
Make-up Loss	5.220 in
Coupling Length	11.732 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	1 069 klb
Compression Yield Load	855 klb
Internal Yield Pressure	11 170 psi
External Pressure Resistance	7 870 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	496 klb

TORQUE VALUES

Minimum Make-up torque	18 210 ft-lb
Optimum Make-up torque	20 230 ft-lb
Maximum Make-up torque	22 260 ft-lb
Minimum Shoulder Torque	1 010 ft-lb
Maximum Shoulder Torque	1 010 ft-lb
Maximum Operational Torque	24 280 ft-lb

Connection qualified as per ISO 13679:2002 - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_One-7.625-33.7-TX28-110

Date of issue (dd/mm/yyyy): 31/10/2024

TUBACEX
GROUP