

6⁵/₈ in 24 lb/ft TX28-110 (N08028)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	6.625 in
Nominal ID	5.921 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.352 in
Minimum Wall Thickness	90 %
Drift	5.796 in

CONNECTION PROPERTIES

Coupling OD (nominal)	7.283 in
Coupling ID (nominal)	5.846 in
Make-up Loss	4.921 in
Coupling Length	10.866 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	763 klb
Compression Yield Load	610 klb
Internal Yield Pressure	10 520 psi
External Pressure Resistance	6 730 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	368 klb

TORQUE VALUES

Minimum Make-up torque	13 010 ft-lb
Optimum Make-up torque	14 460 ft-lb
Maximum Make-up torque	15 900 ft-lb
Minimum Shoulder Torque	720 ft-lb
Maximum Shoulder Torque	720 ft-lb
Maximum Operational Torque	17 350 ft-lb

Connection qualified as per ISO 13679:2002 - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_One-6.625-24-TX28-110

Date of issue (dd/mm/yyyy): 31/10/2024

TUBACEX
GROUP