

### 7<sup>5</sup>/<sub>8</sub> in 42.8 lb/ft TX28-110 (N08028)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

#### PIPE BODY CHARACTERISTICS

Nominal OD	7.625 in
Nominal ID	6.501 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.562 in
Minimum Wall Thickness	90 %
Drift	6.375 in

#### CONNECTION PROPERTIES

Coupling OD (nominal)	8.518 in
Coupling ID (nominal)	6.479 in
Make-up Loss	5.220 in
Coupling Length	11.732 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

#### CONNECTION PERFORMANCE

Tensile Yield Load	1 371 klb
Compression Yield Load	1 097 klb
Internal Yield Pressure	14 590 psi
External Pressure Resistance	13 930 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	741 klb

#### TORQUE VALUES

Minimum Make-up torque	25 700 ft-lb
Optimum Make-up torque	28 560 ft-lb
Maximum Make-up torque	31 420 ft-lb
Minimum Shoulder Torque	1 430 ft-lb
Maximum Shoulder Torque	1 430 ft-lb
Maximum Operational Torque	34 280 ft-lb

Connection qualified as per ISO 13679:2002 - CAL IV



[www.sentinelconnections.com](http://www.sentinelconnections.com)

PCTDS-SENTINEL\_One-7.625-42.8-TX28-110

Date of issue (dd/mm/yyyy): 31/10/2024

**TUBACEX**  
GROUP