

7 in 35 lb/ft TX28-110 (N08028)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	7.000 in
Nominal ID	6.004 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.498 in
Minimum Wall Thickness	90 %
Drift	5.879 in

CONNECTION PROPERTIES

Coupling OD (nominal)	7.815 in
Coupling ID (nominal)	5.932 in
Make-up Loss	4.761 in
Coupling Length	11.535 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	1 119 klb
Compression Yield Load	895 klb
Internal Yield Pressure	14 090 psi
External Pressure Resistance	13 030 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	609 klb

TORQUE VALUES

Minimum Make-up torque	20 510 ft-lb
Optimum Make-up torque	22 790 ft-lb
Maximum Make-up torque	25 070 ft-lb
Minimum Shoulder Torque	1 140 ft-lb
Maximum Shoulder Torque	1 140 ft-lb
Maximum Operational Torque	27 350 ft-lb

Connection qualified as per ISO 13679:2002 - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_One-7-35-TX28-110

Date of issue (dd/mm/yyyy): 31/10/2024

TUBACEX
GROUP