

4½ in 11.6 lb/ft TX28-125 (N08028)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	4.500 in
Nominal ID	4.000 in
Min. Yield Strength	125 ksi
Nominal Wall Thickness	0.250 in
Minimum Wall Thickness	90 %
Drift	3.875 in

CONNECTION PROPERTIES

Coupling OD (nominal)	4.902 in
Coupling ID (nominal)	3.952 in
Make-up Loss	3.342 in
Coupling Length	7.441 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	417 klb
Compression Yield Load	334 klb
Internal Yield Pressure	12 500 psi
External Pressure Resistance	8 000 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	161 klb

TORQUE VALUES

Minimum Make-up torque	4 380 ft-lb
Optimum Make-up torque	4 870 ft-lb
Maximum Make-up torque	5 350 ft-lb
Minimum Shoulder Torque	240 ft-lb
Maximum Shoulder Torque	240 ft-lb
Maximum Operational Torque	4 870 ft-lb

Connection qualified as per ISO 13679:2002 - CAL IV

