

7⁵/₈ in 29.7 lb/ft TX28-125 (N08028)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	7.625 in
Nominal ID	6.875 in
Min. Yield Strength	125 ksi
Nominal Wall Thickness	0.375 in
Minimum Wall Thickness	90 %
Drift	6.750 in

CONNECTION PROPERTIES

Coupling OD (nominal)	8.213 in
Coupling ID (nominal)	6.810 in
Make-up Loss	5.220 in
Coupling Length	11.732 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	1 067 klb
Compression Yield Load	854 klb
Internal Yield Pressure	11 070 psi
External Pressure Resistance	5 670 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	444 klb

TORQUE VALUES

Minimum Make-up torque	18 520 ft-lb
Optimum Make-up torque	20 580 ft-lb
Maximum Make-up torque	22 640 ft-lb
Minimum Shoulder Torque	1 030 ft-lb
Maximum Shoulder Torque	1 030 ft-lb
Maximum Operational Torque	20 580 ft-lb

Connection qualified as per ISO 13679:2002 - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_One-7.625-29.7-TX28-125

Date of issue (dd/mm/yyyy): 31/10/2024

TUBACEX
GROUP