

4½ in 12.6 lb/ft TX25NP-80 (S32750)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	4.500 in
Nominal ID	3.958 in
Min. Yield Strength	80 ksi
Nominal Wall Thickness	0.271 in
Minimum Wall Thickness	87.5 %
Drift	3.833 in

CONNECTION PROPERTIES

Coupling OD (nominal)	4.937 in
Coupling ID (nominal)	3.898 in
Make-up Loss	3.521 in
Coupling Length	7.913 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	288 klb
Compression Yield Load	288 klb
Internal Yield Pressure	8 430 psi
External Pressure Resistance	7 500 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	157 klb

TORQUE VALUES

Minimum Make-up torque	5 580 ft-lb
Optimum Make-up torque	6 200 ft-lb
Maximum Make-up torque	6 820 ft-lb
Minimum Shoulder Torque	310 ft-lb
Maximum Shoulder Torque	4 340 ft-lb
Maximum Operational Torque	7 100 ft-lb

Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_Prime-4.5-12.6-TX25NP-80

Date of issue (dd/mm/yyyy): 31/10/2024

TUBACEX
GROUP