

5½ in 20 lb/ft TX25NP-80 (S32750)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	5.500 in
Nominal ID	4.778 in
Min. Yield Strength	80 ksi
Nominal Wall Thickness	0.361 in
Minimum Wall Thickness	87.5 %
Drift	4.653 in

CONNECTION PROPERTIES

Coupling OD (nominal)	6.098 in
Coupling ID (nominal)	4.709 in
Make-up Loss	4.535 in
Coupling Length	10.472 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	466 klb
Compression Yield Load	466 klb
Internal Yield Pressure	9 190 psi
External Pressure Resistance	8 830 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	262 klb

TORQUE VALUES

Minimum Make-up torque	9 010 ft-lb
Optimum Make-up torque	10 010 ft-lb
Maximum Make-up torque	11 010 ft-lb
Minimum Shoulder Torque	500 ft-lb
Maximum Shoulder Torque	7 010 ft-lb
Maximum Operational Torque	11 270 ft-lb

Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_Prime-5.5-20-TX25NP-80

Date of issue (dd/mm/yyyy): 31/10/2024

TUBACEX
GROUP