

5½ in 17 lb/ft TX28-110 (N08028)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	5.500 in
Nominal ID	4.892 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.304 in
Minimum Wall Thickness	90 %
Drift	4.767 in

CONNECTION PROPERTIES

Coupling OD (nominal)	6.006 in
Coupling ID (nominal)	4.823 in
Make-up Loss	4.535 in
Coupling Length	10.472 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	546 klb
Compression Yield Load	437 klb
Internal Yield Pressure	10 940 psi
External Pressure Resistance	7 480 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	212 klb

TORQUE VALUES

Minimum Make-up torque	8 630 ft-lb
Optimum Make-up torque	9 580 ft-lb
Maximum Make-up torque	10 540 ft-lb
Minimum Shoulder Torque	480 ft-lb
Maximum Shoulder Torque	6 710 ft-lb
Maximum Operational Torque	11 820 ft-lb

Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_Prime-5.5-17-TX28-110

Date of issue (dd/mm/yyyy): 31/10/2024

TUBACEX
GROUP