

### 5½ in 20 lb/ft TX28-125 (N08028)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

#### PIPE BODY CHARACTERISTICS

Nominal OD	5.500 in
Nominal ID	4.778 in
Min. Yield Strength	125 ksi
Nominal Wall Thickness	0.361 in
Minimum Wall Thickness	90 %
Drift	4.653 in

#### CONNECTION PROPERTIES

Coupling OD (nominal)	6.098 in
Coupling ID (nominal)	4.709 in
Make-up Loss	4.535 in
Coupling Length	10.472 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

#### CONNECTION PERFORMANCE

Tensile Yield Load	729 klb
Compression Yield Load	583 klb
Internal Yield Pressure	14 770 psi
External Pressure Resistance	12 080 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	328 klb

#### TORQUE VALUES

Minimum Make-up torque	12 370 ft-lb
Optimum Make-up torque	13 740 ft-lb
Maximum Make-up torque	15 110 ft-lb
Minimum Shoulder Torque	690 ft-lb
Maximum Shoulder Torque	9 620 ft-lb
Maximum Operational Torque	13 740 ft-lb

Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV



[www.sentinelconnections.com](http://www.sentinelconnections.com)

PCTDS-SENTINEL\_Prime-5.5-20-TX28-125

Date of issue (dd/mm/yyyy): 31/10/2024

**TUBACEX**  
GROUP