

### 4½ in 13.5 lb/ft TX825-110 (N08825)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

#### PIPE BODY CHARACTERISTICS

Nominal OD	4.500 in
Nominal ID	3.920 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.290 in
Minimum Wall Thickness	90 %
Drift	3.795 in

#### CONNECTION PROPERTIES

Coupling OD (nominal)	4.986 in
Coupling ID (nominal)	3.859 in
Make-up Loss	3.521 in
Coupling Length	7.913 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

#### CONNECTION PERFORMANCE

Tensile Yield Load	422 klb
Compression Yield Load	338 klb
Internal Yield Pressure	12 760 psi
External Pressure Resistance	10 690 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	206 klb

#### TORQUE VALUES

Minimum Make-up torque	7 400 ft-lb
Optimum Make-up torque	8 220 ft-lb
Maximum Make-up torque	9 040 ft-lb
Minimum Shoulder Torque	410 ft-lb
Maximum Shoulder Torque	5 750 ft-lb
Maximum Operational Torque	10 130 ft-lb

Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV



[www.sentinelconnections.com](http://www.sentinelconnections.com)

PCTDS-SENTINEL\_Prime-4.5-13.5-TX825-110

Date of issue (dd/mm/yyyy): 31/10/2024

**TUBACEX**  
GROUP