

### 7 in 32 lb/ft TX825-125 (N08825)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

#### PIPE BODY CHARACTERISTICS

Nominal OD	7.000 in
Nominal ID	6.094 in
Min. Yield Strength	125 ksi
Nominal Wall Thickness	0.453 in
Minimum Wall Thickness	90 %
Drift	6.000 in

#### CONNECTION PROPERTIES

Coupling OD (nominal)	7.732 in
Coupling ID (nominal)	6.055 in
Make-up Loss	4.954 in
Coupling Length	11.339 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

#### CONNECTION PERFORMANCE

Tensile Yield Load	1 165 klb
Compression Yield Load	932 klb
Internal Yield Pressure	14 560 psi
External Pressure Resistance	11 710 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	603 klb

#### TORQUE VALUES

Minimum Make-up torque	23 970 ft-lb
Optimum Make-up torque	26 630 ft-lb
Maximum Make-up torque	29 300 ft-lb
Minimum Shoulder Torque	1 330 ft-lb
Maximum Shoulder Torque	18 650 ft-lb
Maximum Operational Torque	26 630 ft-lb

Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV



[www.sentinelconnections.com](http://www.sentinelconnections.com)

PCTDS-SENTINEL\_Prime-7-32-TX825-125

Date of issue (dd/mm/yyyy): 31/10/2024

**TUBACEX**  
GROUP