

9⁵/₈ in 47 lb/ft TX825-125 (N08825)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	9.625 in
Nominal ID	8.681 in
Min. Yield Strength	125 ksi
Nominal Wall Thickness	0.472 in
Minimum Wall Thickness	90 %
Drift	8.525 in

CONNECTION PROPERTIES

Coupling OD (nominal)	10.502 in
Coupling ID (nominal)	8.634 in
Make-up Loss	5.487 in
Coupling Length	12.795 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	1 697 klb
Compression Yield Load	1 357 klb
Internal Yield Pressure	11 030 psi
External Pressure Resistance	5 630 psi
Max. Bending with API Sealability	10 °/100 ft
Max. Load on Coupling Face	948 klb

TORQUE VALUES

Minimum Make-up torque	33 670 ft-lb
Optimum Make-up torque	37 410 ft-lb
Maximum Make-up torque	41 150 ft-lb
Minimum Shoulder Torque	1 870 ft-lb
Maximum Shoulder Torque	26 180 ft-lb
Maximum Operational Torque	37 410 ft-lb

Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_Prime-9.625-47-TX825-125

Date of issue (dd/mm/yyyy): 31/10/2024

TUBACEX
GROUP