

5½ in 20 lb/ft TXG3-110 (N06985)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	5.500 in
Nominal ID	4.778 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.361 in
Minimum Wall Thickness	90 %
Drift	4.653 in

CONNECTION PROPERTIES

Coupling OD (nominal)	6.098 in
Coupling ID (nominal)	4.709 in
Make-up Loss	4.535 in
Coupling Length	10.472 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	641 klb
Compression Yield Load	513 klb
Internal Yield Pressure	13 000 psi
External Pressure Resistance	11 100 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	289 klb

TORQUE VALUES

Minimum Make-up torque	11 220 ft-lb
Optimum Make-up torque	12 470 ft-lb
Maximum Make-up torque	13 720 ft-lb
Minimum Shoulder Torque	630 ft-lb
Maximum Shoulder Torque	8 730 ft-lb
Maximum Operational Torque	15 390 ft-lb

Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_Prime-5.5-20-TXG3-110

Date of issue (dd/mm/yyyy): 31/10/2024

TUBACEX
GROUP