

7 in 26 lb/ft TXG3-110 (N06985)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

PIPE BODY CHARACTERISTICS

Nominal OD	7.000 in
Nominal ID	6.276 in
Min. Yield Strength	110 ksi
Nominal Wall Thickness	0.362 in
Minimum Wall Thickness	90 %
Drift	6.151 in

CONNECTION PROPERTIES

Coupling OD (nominal)	7.583 in
Coupling ID (nominal)	6.213 in
Make-up Loss	4.954 in
Coupling Length	11.339 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCE

Tensile Yield Load	830 klb
Compression Yield Load	664 klb
Internal Yield Pressure	10 240 psi
External Pressure Resistance	6 230 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	373 klb

TORQUE VALUES

Minimum Make-up torque	17 180 ft-lb
Optimum Make-up torque	19 080 ft-lb
Maximum Make-up torque	20 990 ft-lb
Minimum Shoulder Torque	950 ft-lb
Maximum Shoulder Torque	13 360 ft-lb
Maximum Operational Torque	22 070 ft-lb

Connection qualified as per API RP 5C5 4th edition (2017) - CAL IV



www.sentinelconnections.com

PCTDS-SENTINEL_Prime-7-26-TXG3-110

Date of issue (dd/mm/yyyy): 31/10/2024

TUBACEX
GROUP