

## 6<sup>5</sup>/<sub>8</sub> in 28 lb/ft TX28-125 (N08028)

Box end finish: Cu-Plating Lubrication: API-Modified

Clearance: Standard Bevel: 45°

### PIPE BODY CHARACTERISTICS

Nominal OD	6.625 in
Nominal ID	5.791 in
Min. Yield Strength	125 ksi
Nominal Wall Thickness	0.417 in
Minimum Wall Thickness	90 %
Drift	5.666 in

### CONNECTION PROPERTIES

Coupling OD (nominal)	7.299 in
Coupling ID (nominal)	5.717 in
Make-up Loss	4.921 in
Coupling Length	10.866 in
Tension Efficiency	100 % of pipe
Compression Efficiency	100 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

### CONNECTION PERFORMANCE

Tensile Yield Load	1 016 klb
Compression Yield Load	813 klb
Internal Yield Pressure	14 160 psi
External Pressure Resistance	10 990 psi
Max. Bending with API Sealability	20 °/100 ft
Max. Load on Coupling Face	436 klb

### TORQUE VALUES

Minimum Make-up torque	15 930 ft·lb
Optimum Make-up torque	17 700 ft·lb
Maximum Make-up torque	19 470 ft·lb
Minimum Shoulder Torque	890 ft·lb
Maximum Shoulder Torque	12 390 ft·lb
Maximum Operational Torque	21 240 ft·lb

Connection qualified as per ISO 13679:2002 - CAL IV



[www.sentinelconnections.com](http://www.sentinelconnections.com)

PCTDS-SENTINEL\_One-6.625-28-TX28-125

Date of issue (dd/mm/yyyy): 07/02/2025

**TUBACEX**  
GROUP